






Wendeschneidplatten

positiv, mit Planschneiden
allseitig präzisionsgeschliffen

Darstellung	ISO-Bezeichnung	l	d	s	bf	α
Grundabmessungen	TPGN 10.02.02 TPGN 11.03.04 TPGN 16.03.00 TPGN 22.03.12 TPGN 22.04.12	10,4 11 16 22 22	6,0 6,35 9,525 12,7 12,7	2,38 3,18 3,18 3,18 4,76	- - - - -	11° 11° 11° 11° 11°
    	TPAN 11.03.PC ident. mit P 602/0 TPAN 16.03.PP ident. mit P 602/1 TPAN 22.04.PP ident. mit P 602/3 TPKN 16.03.PPR ident. mit P 603/1 TPKN 22.04.PP ident. mit P 603/3 TPAN 16.03.PPN ident. mit R 273.7-1220 TPKN 16.03.PPR ident. mit R 273.4-1220 TPKN 16.03.PPL ident. mit L 273.4-1220 TPKN 22.04.PDR ident. mit R 273.4-1630 TPKN 22.04.PDL ident. mit L 273.4-1630 TFAN 22.03.PFR	11 16 22 16 22 16 16 22 22 22	6,35 9,525 12,7 9,525 12,7 9,525 9,525 12,7 12,7 12,7	3,18 3,18 4,76 3,18 3,18 3,18 3,18 4,76 4,76 3,18	1,0 1,2 1,2 1,2 1,2 1,2 1,4 1,4 2,5	11° 11° 11° 11° 11° 11° 11° 11° 11° 25°
mit Spanformstufen	TPHD 10.02.FP.R/10°/12° mit 3 re Spanformstufen, Spanwinkel 12° und Kugelkalotte TPHD 15.03.FP.R/10°/12°-9,2 mit 3 re Spanformstufen, Spanwinkel 12° und Kugelkalotte	10,4 15,93	6,0 9,2	2,38 3,18	0,5 0,7	10° 10°